



ТЕХНИЧЕСКОЕ ОПИСАНИЕ

AIMOL Hydraulic Oil HVLP

AIMOL Hydraulic Oil HVLP-

AIMOL Hydraulic Oil HVLP

DIN 51524

3 (HVLP),

- ◆
- ◆
- ◆
- ◆
- ◆
- ◆
- ◆
- ◆
- ◆
- ◆
- ◆
- ◆
- ◆
- ◆
- ◆
- ◆
- ◆

HVLP

AIMOL Hydraulic Oil HVLP -

- ◆ DIN 51524 3 (HVLP)
- ◆ ISO 6743/4 HV
- ◆ Denison HF-0, HF-1, HF-2
- ◆ AFNOR NF E 48-603 HV
- ◆ Eaton Vickers M-2950S, +286
- ◆ Cincinatti Milacron P68/P69
- ◆ Bosch Rexroth 90220



ТЕХНИЧЕСКОЕ ОПИСАНИЕ

AIMOL Hydraulic Oil HVLP

		32	46
20 °C, /	ASTM D1298	0.872	0.878
	ASTM D97	192	203
-30 °C,	ASTM D4052	2912.2	6206.7
-20 °C,	ASTM D4052	1097.5	2126.3
0 °C,	ASTM D4052	237.8	397.4
40 °C,	ASTM D445	33.1	46
100 °C,	ASTM D445	6.75	8.2
	ASTM D2270	167	154
°C	ASTM D97	-50	-45
/	ASTM D664	0.6	0.6
FZG	FZG A/8.3/90	11	11
	ISO 4406	17/14/11	
ASTM D943,	ASTM D943	>2000	>2000

AIMOL Hydraulic Oil HVLP -

AIMOL

AIM b.v.