



ТЕХНИЧЕСКОЕ ОПИСАНИЕ

AIMOL Hydroline HVLP

AIMOL Hydroline HVLP -

AIMOL Hydroline HVLP



(2,5

HVLP)

AIMOL Hydroline HVLP -

- ◆ DIN 51524 3 (HVLP)
- ◆ Vickers I-286-S/ M-2950-S
- ◆ ISO L-HV (ISO 6743/4)
- ◆ VDMA 24318

- ◆ US Steel 126/127
- ◆ Thyssen TH-N-256132
- ◆ Afnor NF E 48603 (HV)
- ◆ Cincinnati Milacron P68/P69/P70 (ISO VG 32/46/68)



ТЕХНИЧЕСКОЕ ОПИСАНИЕ

AIMOL Hydroline HVLP

		15	22	32	46	68	100
15 °C, /	ASTM D1298	0.853	0.859	0.862	0.860	0.869	0.880
, °C	ASTM D92	180	195	211	213	216	231
-30 °C,	ASTM D4052	789.5	1731.1	3057.5	-	-	-
-20 °C,	ASTM D4052	332.0	666.2	1122.2	2123.8	3808.4	-
0 °C,	ASTM D4052	86.6	151.1	234.7	399.4	655.7	1109.3
40 °C,	ASTM D445	15.6	22.8	31.6	46.4	67.0	101
100 °C,	ASTM D445	3.9	5.0	6.3	8.2	10.6	14.3
	ASTM D2270	151	153	155	152	147	146
°C	ASTM D97	-42	-39	-36	-33	-30	-27
/	ASTM D664	0.9	0.9	0.9	0.9	0.9	0.9
, %	ASTM D874	0.15	0.15	0.15	0.15	0.15	0.15
FZG	FZG A/8.3/90	10	10	12	>12	>12	>12
ASTM D943,	ASTM D943	>2000	>2000	>2000	>2000	>2000	>2000
	ISO 4406	20/18/14					

AIMOL Hydroline HVLP -

AIMOL

AIM b.v.