



ТЕХНИЧЕСКОЕ ОПИСАНИЕ

AIMOL Airtech HC

AIMOL Airtech HC



DIN 51506 VDL

AIMOL Airtech HC

| | | | | | | |
|---------------------|------------|---------|---------|---------|---------|---------|
| | | 32 | 46 | 68 | 100 | 150 |
| | ASTM D2270 | 101 | 102 | 102 | 99 | 114 |
| 40°C, | ASTM D445 | 34 | 46 | 67 | 103 | 152 |
| 100°C, | ASTM D445 | 5.6 | 6.8 | 8.7 | 11.5 | 16.4 |
| , °C | ASTM D92 | 214 | 218 | 221 | 226 | 246 |
| , °C | ASTM D92 | 322 | 381 | 385 | 403 | 417 |
| , °C | ASTM D97 | -34 | -32 | -30 | -30 | -24 |
| , 24 | ASTM D130 | 1a | 1a | 1a | 1 | 1 |
| 55 °C, 30 | ASTM D140 | 40/40/0 | 40/40/0 | 40/40/0 | 40/40/0 | 40/40/0 |
| • | ASTM D4172 | 0.45 | 0.45 | 0.44 | 0.44 | 0.40 |
| • 1200 / 750 , 40 , | ASTM D2596 | 100 | 100 | 100 | 100 | 100 |
| (/) | - | | | | | |



ТЕХНИЧЕСКОЕ ОПИСАНИЕ

AIMOL Airtech HC

AIMOL Airtech HC -

AIMOL

AIM b.v.



zakaz@arsenal-oil.ru

8(495)760-38-56

8(812)954-34-40

8(800)500-1945

www.arsenal-oil.ru