



## ТЕХНИЧЕСКОЕ ОПИСАНИЕ

### AIMOL Hydraulic Oil HLP

AIMOL Hydraulic Oil HLP-

HLP

HLP DIN

51524

AIMOL Hydraulic Oil HLP -

- ◆ DIN 51524 2 (HLP)
- ◆ ISO 11158 HM
- ◆ ISO 20763 (Conestoga)
- ◆ Bosch Rexroth 90220
- ◆ Eaton Vickers M-2950-S (35VQ25)
- ◆ Eaton Vickers I-286 S3 ( )

- ◆ Vickers 35VQ25
- ◆ Denison HF-0, HF-1 HF-2 (T6H20C)
- ◆ Cincinnati Milacron P-68, P-69, P-7
- ◆ JCMAS P041 HK
- ◆ ANSI/AGMA 9005-E02-RO
- ◆ GM LS-2;
- ◆ US Steel 126/127 (AIST)
- ◆ SEB 181222



## ТЕХНИЧЕСКОЕ ОПИСАНИЕ

### AIMOL Hydraulic Oil HLP

		HLP 32	HLP 46	HLP 68
20° C, / <sup>3</sup>	ASTM D1298	873	879	882
, ° C	ASTM D92	216	220	228
-20° C,	ASTM D4052	2292.8	-	-
0° C,	ASTM D4052	336.1	761.5	1360.0
40° C,	ASTM D445	32	46	68
100° C,	ASTM D445	5.4	6.7	8.6
	ASTM D2270	100	99	98
° C	ASTM D97	-32	-28	-26
3 100 <sup>0</sup>	ASTM D 130	1a	1a	1a
ASTM D943,	ASTM D943	>2000	>2000	>2000
	ISO 4406	16/13/10		

AIMOL Hydraulic Oil HLP -

AIMOL

AIM b.v.